



GatorSeal®

GRANULAR SELF-ADHERED ICE & WATER PROTECTION



- · Modified asphalt reinforced with an extra heavy fiberglass mat
- Uniformly seals to the deck and around fastener penetrations
- UV protected surface
- Helps to protect building from damage due to ice dams and wind driven rain
- Aggressive bond at low temperatures

Features and Benefits



Durable Protection – All Season

Heavy duty fiberglass reinforcement provides strength and durability. The proprietary modified asphalt helps to prevent moisture penetration and damage due to wind, rain, ice and snow. Opaque granules on the surface provide great traction during installation and protect against UV. Sealing direct to the roof deck makes GatorSeal® Ice & Water Underlayment a good choice for those critical areas of the roof such as valleys, perimeters, eaves, chimneys, walls, dormers and skylights.



Easy Installation

No heat, special tools or equipment are required to install GatorSeal® in cold or warm climates. The selfadhered layer is covered with a release sheet, easily removed during installation to permanently bond to the roof deck or base sheet.



Product Performance

20 year limited warranty under tile, stone coated steel or shingle. GatorSeal® Ice & Water Underlayment meets or exceeds all national and Florida building code requirements and consistently outperforms conventional underlayments.



Build a customized truck load for any combination of the following products:

- Westlake Royal TileSeal[™] HT
- Westlake Royal[™] MetalSeal HT
- GatorSeal®
- Citadel® Plus

Call Customer Service for more information or to build your customized truck load.

SPECIFICATIONS

Roll Size 3' x 66.7' (200 sq ft) **Roll Weight** 57 lbs (nominal) 2 squares Coverage **Thickness** 46 mils (nominal) Rolls per pallet 30 Rolls

Pallet weight 1,760 lbs (nominal) **CERTIFICATIONS / APPROVALS**

Florida FL14317 **ASTM** D1970

PART NUMBERS

91753 2 Square Roll

91746 Drop Ship Full Truck - 780 Rolls 92632 Drop Ship Mixed Truck - 780 Rolls

NOTE: This product is not recommended for use on roofs with tiles installed without battens. When loading tiles onto GatorSeal®, make sure the tiles are supported by properly fastened battens to prevent tiles from sliding down the roof slope.

