

Zephyr Block™

INSTALLATION GUIDE

The following guidelines are provided to insure proper installation of Zephyr Block™, however local building codes may differ so please consult with the local building department for any different or additional installation requirements.

Tile surface must be clean and dry to ensure adhesion of Zephyr Block's butyl adhesive. Install when ambient temperatures are between 41°F to 104°F.

1. Install Ridge Riser® brackets no greater than 24 inches apart. Ridge Riser® is pre-scored at three locations to accommodate all profiles and roof pitches. Ridge Riser must be installed prior to the last course of battens and roof tile.
2. Place a 2" x 2" wood nailer board into Ridge Riser® bracket. Fasten wood nailer to Ridge Riser® brackets with a #8 3/4 inch screw or nail.
3. **Alternative Option:** A solid ridge nailer board may be toe nailed into the rafters in place of Ridge Riser® brackets with 2" x 2" ridge nailer, but this may require a 3/4 inch or greater cut back of decking at the ridge for sufficient minimum 3/8 inch opening on each side of the ridge board.
4. Attach the last row of battens and top course of field tiles. Place a trim piece of tile at both ends of the ridge or hip, strike a line on outside of the trim tile both sides, this will ensure the Zephyr Block™ does not over extend the width of the trim tile.
5. Roll out and align Zephyr Block™ starting at one end on ridge or hip board and fasten through the centerline on the Zephyr Block™ onto the top of the ridge or hip board, butyl strip down. **(Pic. 1)** Allow for 6 inch overhang at gable fold onto Gable and fasten. When starting another new roll the connecting parts must overlap at least 2 inches.
Note: keep roll out of direct heat or sunlight, prior to application to allow easier release of the plastic release film from the butyl adhesive strips.
6. Remove the plastic release film from the butyl adhesive **(Pic. 2)** and form to the top surface of the last course of field tile at the pre marked strike chalk line and form the adhesive strip using your fingers. Carefully shape and press the side strips - only at the edges where the butyl adhesive is applied - to the profile of the tiles. **(Pic. 3)** It is important to start at each highest point on a high profile roof tile.
7. Attach trim tiles on ridge and hips. **(Pic. 4)**

